



TLB
Digital / Analog weight Transmitter RS485



MODBUS RTU



DESCRIPTION

- Weight transmitters suitable for back panel mounting on Omega / DIN rail.
- Space-saving vertical shape.
- Dimensions: 25x115x120 mm.
- 6-digit semi-alphanumeric red LED display (8 mm height).
- 6 signalling LED.
- Four buttons for the system calibration.
- Extractable screw terminal blocks.

INPUTS/OUTPUTS AND COMMUNICATION

- RS485 serial port for communication via protocols ModBus RTU, ASCII Laumas bidirectional or continuous one way transmission.
- 3 relay outputs controlled by the setpoint values or via protocols.
- 2 optoisolated PNP digital inputs: status reading via serial communication protocols.
- 1 load cell dedicated input.

FIELD BUSES

MODBUS RTU

MODBUS/TCP

ETHERNET
POWERLINK
certified product

DeviceNet

EtherNet/IP

PIV CERTIFIED
PROFIBUS - PROFINET

PROFIBUS

CC-Link

CANopen

SERCOS
interface

ETHERNET
TCP/IP

EtherCAT

	DESCRIPTION	CODE
	<p>RS485 serial port. Baud rate: 2400, 4800, 9600, 19200, 38400, 115200 (bit/s).</p>	TLB485
	<p>Optoisolated 16 bit analog output. Current: 0÷20 mA; 4÷20 mA (up to 300 Ω). Voltage: 0÷10 V; 0÷5 V; ±10 V; ±5 V (min 10 k Ω). Equipped with RS485 serial port.</p>	TLB
	<p>CANopen port. Baud rate: 10, 20, 25, 50, 100, 125, 250, 500, 800, 1000 (kbit/s). The instrument works as slave in a synchronous CANopen network. Equipped with RS485 serial port.</p>	TLBCANOPEN
	<p>DeviceNet port. Baud rate: 125, 250, 500 (kbit/s). The instrument works as slave in a DeviceNet network. Equipped with RS485 serial port.</p>	TLBDEVICENET
	<p>CC-Link port. Baud rate: 156, 625, 2500, 5000, 10000 (kbit/s). The instrument works as Remote Device Station in a CC-Link network and occupies 3 stations. Equipped with RS485 serial port.</p>	TLBCCLINK
	<p>PROFIBUS DP port. Baud rate: up to 12 Mbit/s. The instrument works as slave in a Profibus-DP network. Equipped with RS485 serial port.</p>	TLBPROFI
	<p>Modbus/TCP port. Type: RJ45 10Base-T or 100Base-TX (auto-sensing). The instrument works as slave in a Modbus/TCP network. Equipped with RS485 serial port.</p>	TLBMODBUSTCP
	<p>Ethernet TCP/IP port. Type: RJ45 10Base-T or 100Base-TX (auto-sensing). The instrument works in an Ethernet TCP/IP network and it is accessible via web browser. Equipped with RS485 serial port.</p>	TLBETHETCP
	<p>2x Ethernet/IP ports. Type: RJ45 10Base-T or 100Base-TX (auto-sensing). The instrument works as adapter in an Ethernet/IP network. Equipped with RS485 serial port.</p>	TLBETHEIP
	<p>2x PROFINET IO ports. Type: RJ45 100Base-TX. The instrument works as device in a Profinet IO network. Equipped with RS485 serial port.</p>	TLBPROFINETIO
	<p>2x EtherCAT ports. Type: RJ45 10Base-T or 100Base-TX (auto-sensing). The instrument works as slave in an EtherCAT network. Equipped with RS485 serial port.</p>	TLBETHERCAT
	<p>2x POWERLINK ports. Type: RJ45 10Base-T or 100Base-TX (auto-sensing). The instrument works as slave in a Powerlink network. Equipped with RS485 serial port.</p>	TLBPOWERLINK
	<p>2x SERCOS III ports. Type: RJ45 10Base-T or 100Base-TX (auto-sensing). The instrument works as slave in a Sercos III network. Equipped with RS485 serial port.</p>	TLBSERCOS



CERTIFICATIONS



OIML R76:2006, class III, 3x10000 divisions, 0.2 $\mu\text{V}/\text{VSI}$ / OIML R61 - WELMEC Guide 8.8:2011 (MID)

CERTIFICATIONS ON REQUEST

M	Initial verification in combination with Laumas weighing module
cRU_{us}	UL Recognized component - Complies with the United States and Canada standards
EAC	Complies with the Eurasian Custom Union standards
NTEP	NTEP - n_{max} 5000 - Class III - United States and Canada

TECHNICAL FEATURES


Power supply and consumption	12÷24 VDC $\pm 10\%$; 5 W	
Number of load cells · Load cells supply	up to 8 (350 Ω) - 4/6 wires · 5 VDC/120 mA	
Linearity · Analog output linearity (only for TLB)	< 0.01% full scale · < 0.01% full scale	
Thermal drift · Analog output thermal drift (only for TLB)	<0.0005% full scale/°C · <0.003% full scale/°C	
A/D Converter	24 bit (16000000 points) - 4.8 kHz	
Divisions (with measurement range ± 10 mV and sensitivity 2 mV/V)	± 999999 · 0.01 $\mu\text{V}/\text{d}$	
Measurement range	± 39 mV	
Usable load cells sensitivity	± 7 mV/V	
Conversions per second	300/s	
Display range	± 999999	
Decimals · Display increments	0÷4 · x1 x2 x5 x10 x20 x50 x100	
Digital filter · Readings per second	10 levels · 5÷ 300 Hz	
Relay outputs	3 - max 115 VAC /150 mA	
Optoisolated digital inputs	2 - 5÷24 VDC PNP	
Serial ports	RS485	
Baud rate	2400, 4800, 9600, 19200, 38400, 115200 (bit/s)	
Optoisolated analog output (only for TLB)	16 bit = 65535 divisions. 0÷20 mA; 4÷20 mA (up to 300 Ω) 0÷10 V; 0÷5 V; ± 10 V; ± 5 V (min 10 k Ω)	
Humidity (condensate free)	85%	
Storage temperature	-30°C +80°C	
Working temperature	-20°C +60°C	
cRU_{us}	Relay outputs	3 - max 30 VAC , 60 VDC /150 mA
	Working temperature	-20°C +50°C
	Power supply device marked "LPS" (limited power source) or "Class 2"	

METROLOGICAL SPECIFICATIONS OF TYPE-APPROVED INSTRUMENTS

Applied standards	2014/31/UE - EN45501:2015 - OIML R76:2006
Operation modes	single interval, multi-interval
Accuracy class	III or IIII
Maximum number of scale verification divisions	10000 (class III); 1000 (class IIII)
Minimum input signal for scale verification division	0.2 $\mu\text{V}/\text{VSI}$
Working temperature	-10°C +40°C

MAIN FUNCTIONS

- Connections to:
 - PLC via analog output or fieldbuses;
 - PC/PLC via RS485 (up to 99 instruments with line repeaters, up to 32 without line repeaters);
 - remote display via RS485;
 - up to 8 load cells in parallel by junction box.
- Digital filter to reduce the effects of weight oscillation.
- Theoretical calibration (via keyboard) and real calibration (with sample weights and the possibility of weight linearization up to 5 points).
- Tare weight zero setting.
- Automatic zero setting at power-on.
- Gross weight zero tracking.
- Semi-automatic tare (net/gross weight) and preset tare.
- Semi-automatic zero.
- Displaying of the maximum weight value reached (peak).
- Direct connection between RS485 and RS232 without converter.
- Hysteresis and setpoint value setting.
- TCP/IP WEB APP
Integrated software in combination with the Ethernet TCP/IP version for remote supervision, management and control of the instrument.



CE-M version: 2014/31/EU-EN45501:2015-OIML R76:2006

- System parameters management protected by qualified access via software (password), hardware or fieldbus.
- Weight subdivisions displaying (1/10 e).
- Two operation mode: single interval or multi-interval.
- Net weight zero tracking.
- Calibration.

SPACE SAVING COMPACT DESIGN



The Company reserves the right to make changes to the technical data, drawings and images without notice.