



# UV Flame detector test lamp

## *Salwico UV test lamp*

Part no. 1155

System: All Salwico fire alarms

### Description

Salwico UV test lamp is used to perform function test on Salwico UV flame detectors.

Salwico UV test lamp is delivered complete with rechargeable batteries and a battery charger.

### Detector test

Before a test is carried out make sure the flame detector is switched on and the alarm outputs are in override.

Switch on the test lamp. Point at the UV detector within range until the detector indicates alarm with the red LED. Most flame detectors will respond within 30 seconds.

### Charging

The battery is already charged when leaving the factory. However, the unit should always be charged after purchase. See instruction on the back of the charger.

### Data

Ingress protection	IP20
Temperature range	-15°C to +40°C
Material	Plastic
Weight	~2000 g
Test range	Up to 15 meters
Battery charger	100-240 VAC (Lead Acid battery charger, max 1,3A)
Battery type	6V 4,5A
Dimension	300x140x180 mm
Lamp	H3, VDC, 35W
Operation time	2 hours under normal condition up to 15 meters.

### Cautions:

- Do not point directly at eyes from a short distance.
- Do not use lamp in wet conditions.
- Do not remove the protective grate.
- The grate may be hot after use.
- Only for use in safe areas.
- Store in clean, dry space.
- Keep away from children.
- The lamp should not be used when damaged.

### Exchangeable AC plugs



The charger is delivered with adapters for Europe, United States, Australia and United Kingdom.