

Peristaltic pumps TP16 series


The Fluid-o-Tech[®] peristaltic pump technology of the TP16 series, thanks to its extreme compactness and the elimination of the traditional gear box, are a very interesting solution for integration in fluidic systems.

The pump head can be replaced quickly. The unit is available with 12V and 24V drives.

The TP16 Fluid-o-Tech[®] series provides outstanding suction and repeatable performance, making it ideal for dosing applications. The tube is the only material in contact with the fluid, ensuring isolation of the fluid from other parts of the pump and therefore preventing contamination risks.

Advantages:

- Elimination of gear box
- Wide range of tubing materials



MAIN APPLICATIONS


- Dosing in food industry (beverage/condiments)
- Distribution & filling in the cosmetics industry
- Detergent dispense in industrial cleaning equipment
- Analysers and samplers
- Portable equipment

CE


TECHNICAL INFORMATION

Flow rate	20 to 65 ml/min	Tube dimensions * (Øi x Øe)	1.4 x 2.8 mm
Tubing material*	Santoprene/Silicone/Tygon	Unit weight	100 g

* Alternative tube dimensions and materials are available upon request



www.fluidotech.com



Fluid-o-Tech reserves the right to alter the specifications indicated in this catalogue at any time and without prior notice.

Fluid-o-Tech srl

Via Leonardo da Vinci, 40 20094 Corsico, Milano, Italy Tel. +39 02 9995 01 Fax +39 02 9995 0999 info@fluidotech.it

Fluid-o-Tech Int'l Inc. 161 Atwater St., 06479 Plantsville CT (USA) Tel. +1 (860) 276 9270 Fax +1 (860) 620 0193 info@fluid-o-tech.com

Fluid-o-Tech Int'l Inc. Japan 2nd Floor, 4-3-8, Espoir Todoroki, Todoroki, Setagaya, Tokyo 158-0082 Tel. +81 (0) (3) 6432 1812 Fax +81 (0) (3) 6432 1813 erkkato@fluidotech.jp

Fluid-o-Tech Asia (Shanghai) Co., Ltd. 2/F, Factory building 6 (1), No. 258, Zhijiang Read, Fengxian District, Shanghai City, Z.P.: 201499 China Tel. +86 (021) 67100 838 Fax +86 (021) 67100 605 info@fluidotech-asia.com