



vCOM – COMMUNICATION SYSTEMS
POWERCOM



POWERCOM – KEY HIGHLIGHTS

ADVANTAGES OF DATA TRANSFER

VAHLE Powercom® 485 has an integrated transparent RS485 interface according to Profibus standard on the front side and informs about the current status of the device via three status LEDs. The special VAHLE technology ensures trouble-free operation.

VAHLE COMPLETE SOLUTIONS

VAHLE Powercom® 485 offers simple and easy assembly and integration with other VAHLE systems to provide compact and efficient solutions in one package.

POWERCOM – FUNCTION

VAHLE Powercom® 485 is specially designed for RS485-based bus systems with a transfer speed of 19.2 kbit/s for long distances.

The VAHLE Powercom® 485 unit is integrated into a compact top-hat rail housing with power supply. This makes it easier to choose the installation location, e.g. on electric monorail systems, and also facilitates the installation itself.

VAHLE Powercom® 485 has an integrated transparent RS485 interface on the front that complies with the Profibus standard. Under it are the connectors for a 230V/50 Hz power supply (optionally, 115 V/60 Hz), as well as the 2-pin connector leading to the conductor system.

VAHLE Powercom® 485 is a modem for reliable data transfer in RS485 bus systems over a conductor line with a length of up to approx. 5000 m. It can be used together with installed switches, hubs, hub stations etc. The maximum transfer speed is 19.2 kbit/s.

UNINTERRUPTED DATA TRANSFER

VAHLE Powercom® 485 – Data transmission systems in conjunction with VAHLE conductor bars or sliprings were developed for automated handling systems in material flow technology. They enable the uninterrupted and cost effective data transfer between the central control system and the accompanying automation devices on the conveying vehicles.

QUICK AND TRANSPARENT

VAHLE Powercom® 485 is a modem for reliable data transfer in half-duplex via conductor bars or slipring assemblies. It has a RS 485 interface as a standard, is transparent and does not require BUS-addressing. VAHLE Powercom® 485 provides a direct data transfer.

All conductor systems from the VAHLE catalogue can be used for reliable data transfer with VAHLE Powercom® 485.

Tree, ring, and linear structures with crossings, joints, etc. can be realised. This results in ideal operating conditions on electric monorail systems, rack feeders travelling along curved sections, as well as all rail-guided conveying equipment and collector ring bodies.

Areas of application:

- Crane systems
- Stacker cranes
- Transfer trolleys
- Electric monorail systems

POWERCOM – RANGE OF PRODUCTS

TECHNICAL DATA

ELECTRICAL DATA

Transfer mode	Half-Duplex
Transfer speed.....	19.2 kBit/s
Number of subscribers	According to specification of the bus system used
Suitable bus systems.....	Profibus-DP and FMS in acc. with EN 50170 Vol. 2
Wire type of point-to-point connection (connector on interface)	Twisted pair data cables, shielded, according to bus manufacturer's specifications
Wire type (connection from and at the conductor line).....	Shielded power cable
Displays.....	3 status LEDs for power, RX und TX
Operating voltage.....	230 V / 50 Hz (115V / 60 Hz optional)
Voltage drop.....	±10% max.

MECHANICAL DATA

Housing dimensions	85 x 117 x 110 mm (B x H x T), installed vertically, with ventilation slits at top and bottom, minimum distance to other components: 30 mm
Protection type	IP20
Weight.....	1100 g
Mounting type.....	Installation on top-hat rail EN 50-022-35, installed in a central position on the back of the housing

AMBIENT CONDITIONS

Operating temperature	-20 °C ... +50 °C
Storage temperature.....	-20 °C ... +50 °C

RANGE OF PRODUCTS

Description	Transfer length	Devices per segment	Order No.
VAHLE Powercom® 485 230V	up to 5000 m	64	910108*
VAHLE Powercom® 485 115V	up to 5000 m	64	910109*
VAHLE Powercom® Double filter	-	-	910080
VAHLE Powercom® Terminal resistance	-	-	on request*

* Type of terminal resistance bases on type of conductor line. Please contact our TechSales in any case of need.



Paul Vahle GmbH & Co. KG

Westicker Str. 52
59174 Kamen
Germany

Phone: +49 2307 704-0

Fax: +49 2307 704-444

info@vahle.de

www.vahle.com